

HOSES

HPC

Gen-Spec

MADE IN USA



- Smooth cover
- Reduced OD
- 4000 PSI Single braid
- 225°F. maximum

Gray and Blue are non marking hoses

Part	Hose
6659	3/8" x 50' Black
6660	3/8" x 100' Black
6892	3/8" x 50' Blue
6893	3/8" x 100' Blue
6998	3/8" x 50' Gray
6999	3/8" x 100' Gray

HPC

Smooth Cover



- Male solid and swivel fittings
- 250°F. intermittent
- Orange Bend on 4000 PSI
- Red Bend on 6000 PSI

4000 PSI 1 Wire Braid

Part	Hose
6903	3/8" x 50' Blue
6941	3/8" x 50' Gray
6904	3/8" x 100' Blue
6964	3/8" x 100' Gray

6000 PSI 2 Wire Braid

Part	Hose
6954	3/8" x 50' Blue
6962	3/8" x 50' Gray
6956	3/8" x 100' Blue
6963	3/8" x 100' Gray

Wrapped Cover



4000 PSI

Part	Hose
6282	3/8" x 50' Gray
6274	3/8" x 50' Blue
6283	3/8" x 100' Gray
6281	3/8" x 100' blue

6000 PSI 2 Wire Braid

Part	Hose
6363	3/8" x 50' Gray
6332	3/8" x 50' Blue
6369	3/8" x 100' Gray
6339	3/8" x 100' Blue



Continental

ContiTech

NOTE: FULL rolls may have up to 3 pieces with no piece under 50' If single piece on a roll is requested your order may be delayed and carry a 5% up charge. No fittings.

Black Neptune

1/2" ID 3000 PSI 1 Wire Braid

- Smooth cover
- Black bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
1025	25'	9 lb.
1113	50'	18 lb
3733	100'	35 lb
5076	300'	71 lb.
4208	500'	ROLL

3/8" ID 4000 PSI 1 Wire Braid

- Smooth cover
- Orange bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
6450	15'	4 lb
6874	25'	7 lb
6875	30'	9 lb
6867	50'	13 lb
6868	75'	19 lb
6869	100'	26 lb
6870	150'	39 lb
6871	200'	52 lb
6872	250'	65 lb
6873	300'	78 lb
6713	500'	ROLL

3/8" ID 4500 PSI 2 Wire Braid

- Smooth cover
- Red bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
4923	15'	5 lb
4352	25'	8 lb
1207	50'	15 lb
4221	75'	21 lb
1458	100'	28 lb
4302	150'	35 lb
4158	450'	ROLL

3/8" ID 6000 PSI 2 Wire Braid

- Wrapped cover
- Red bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
6116	25'	8 lb
6165	50'	16 lb
6173	100'	32 lb

2



WARNING: These products can expose you to Butadiene which is known to the state of California to cause cancer and birth defects and other reproductive harm. for more information go to www.P65warnings.ca.gov



BLUE Neptune Non-Marking

1/4" ID 3000 PSI

- Smooth cover
- Black bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
5921	25'	7 lb
5279	50'	13lb
5280	100'	18 lb
1669	500'	ROLL

3/8" ID 4000 PSI 1 Wire Braid

- Smooth cover
- Orange bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
6888	25'	9lb
6889	50'	13lb
6890	75'	18lb
6896	100'	25lb
6898	150'	38lb
6900	200'	56 lb
6899	500'	ROLL

3/8" ID 4500 PSI 2 Wire Braid

- Smooth cover
- Red bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
5567	15'	5lb
5230	25'	7lb
5432	50'	13lb
5032	75'	15lb
5033	100'	25lb
5034	150'	42 lb
5036	450'	ROLL

Gray Neptune Non-Marking

3/8" ID 4000 PSI

- Smooth cover
- Orange bend restrictors
- MPT solid/swivel
- 250°F. maximum



Part	Length	Weight
5908	25'	7 lb
5872	50'	13 lb
5875	75'	19 lb
5873	100'	26 lb
6783	150'	
6734	200'	
3724	300'	ROLL
6590	500'	ROLL

Custom Cut Hoses

Part	Hose	PSI
3445	1/4" Blue Neptune	3000
3693	3/8" Black Neptune	4000
6598	3/8" Blue Neptune	4000
6596	3/8" Gray Neptune	4000
4159	3/8" Black Neptune	4500
2393	3/8" Blue Neptune	4500
6002	3/8" black Neptune	6000
4210	1/2" black Neptune	3000



Installed fittings

Part	Size ID
3048	1/4 hose x 1/4 mpt solid
3049	1/4 hose x 1/4 mpt swivel
3050	3/8 hose x 3/8 MPT Solid
3051	3/8 hose x 3/8 MPT Swivel
3726	1/2 hose x 1/2 MPT Solid
3727	1/2 hose x 1/2 MPT Swivel
2887	1/4" Black Bend Restrictor
5013	3/8" Orange Bend Restrictor
2531	3/8" Red Bend Restrictor
3912	1/2" Black Bend Restrictor



Crimp Fittings Non Installed

Part	Hose
2963	1/4" hose x 1/4 mpt solid
2842	1/4" hose x 1/4 mpt swivel
4151	3/8" hose x 3/8 mpt solid
4152	3/8" hose x 3/8 mpt swivel
2884	1/2" hose x 1/2 mpt solid
2865	1/2" hose x 1/2 mpt swivel
2148	Ferrule for 1/2" hoses



Whip Line/Connector

Whip lines are made from ends of rolls or bulk hoses. Hoses are black, gray and blue. If you need specific color whip lines, order as custom cut above.



4000 PSI

Part	Hose
5830	3/8" x 2'
5893	3/8" x 3'
5894	3/8" x 4'
5907	3/8" x 5'
5362	3/8" x 6'
5566	3/8" x 8'
6497	3/8" x 10'

4500 PSI

Part	Hose
1693	3/8" x 2'
4311	3/8" x 3'
1204	3/8" x 4'
3319	3/8" x 5'
1203	3/8" x 6'
1202	3/8" x 8'



WARNING: These products can expose you to Butadiene which is known to the state of California to cause cancer and birth defects and other reproductive harm. for more information go to www.P65warnings.ca.gov

Whitewater Combo

For pressure washers and steam machines



- MPT solid fittings
- No bend restrictor on 1/2"
- Steam maximum 325° @ 350 PSI
- Hot water max 250° @ 3000 PSI
- 1/2" hose max 250° @ 2500 PSI

Part	Size	Weight
4891	3/8" x 25'	7 lb
1201	3/8" x 50'	13 lb
1553	3/8" x 100'	24 lb
1460	1/2" x 50'	18 lb



Flexsteel® 250 CB Steam



For cleaning, heat control, fire prevention, pumping, thawing, blow out service and hoists in open-end or permanent installation operations

- 250 PSI maximum
- 450°F. maximum

Part	Size
3431	1/2" x 25' w/boss clamp
3188	1/2" x 50' w/boss clamp
3292	Boss hose clamp
3287	Boss stem



Sewer Hoses



Durable thermoplastic construction is flexible and lightweight for cornering around elbows.

Smooth surface cover allows easy access through drain pipes and sewer lines

Part	ID	PSI	Lngh	Temp	Fittings
2560	1/8"	2500	50'	140°	1/8" x 1/4"
2561	1/8"	2900	100'	140°	1/8" x 1/4"
6217	1/4"	4350	50'	212°	1/4" x 1/4"
6215	1/4"	4350	100'	212°	1/4" x 1/4"

Hobby Hoses



- 1/4" ID
- Oil Resistant synthetic rubber
- 3000 PSI maximum
- 140°F. maximum
- Replacement for home owner type machines

Part	Size	Fittings
6125	30'	22mmx22mm



Pulse Hoses



- 1500 PSI maximum
- 250°F. maximum
- One end must be plugged



Part	Product
2499	24" 3/8" MPT x 3/8" FPT
2500	24" 3/8" MPT x plugged

Push-On Hoses



Part	Hose
4016	1/4"
3655	3/8"
4017	1/2"
4964	5/8"
4965	3/4"



PVC Poly Braided Hose

Reduced OD, more flexible and WON'T KINK.

Part	ID	Roll
2417	1/4"	100'



PVC Clear braided Hoses



Part	ID	Roll	PSI
2903	1/4"	25'	250
2904	1/4"	50'	250
2905	1/4"	100'	250
6327	1/4"	300'	250
2906	3/8"	25'	250
2907	3/8"	50'	250
2908	3/8"	100'	250
6208	3/8"	300'	250
2909	1/2"	25'	200
2910	1/2"	50'	200
2911	1/2"	100'	200
2915	5/8"	25'	200
2916	5/8"	50'	200
2917	5/8"	100'	200
2912	3/4"	25'	150
2913	3/4"	50'	150
2914	3/4"	100'	150



Ag Suction Hoses

- PVC tube with rigid PVC helix
- Transparent construction
- 110° @ 68°F 70PSI @ 104°F
- MSHA approved



Part	ID	Length
3111	3/4"	20'
3754	3/4"	100'
4135	1"	20'
4011	1"	100'
4015	1 1/2"	20'
3138	1 1/2"	100'

Orange Ag Hoses



- Ribbed cover for reduced drag
- Orange color
- Non marking
- Lightweight, easily coil after use
- Chemical resistant

Good for lawn spraying, agricultural, vineyard, nursery

Part	ID	Length
3894	1/2"	100'
3899	1/2"	200'
3667	1/2"	300'



Plastic Cable Ties

Part	Size	Color
1782	4"	Natural 18#
1785	8"	Black 40#
1789	11"	Black 50#
1788	11"	Natural 50#
4372	14"	Natural 50#
5636	14"	Natural 120#
2641	18"	Natural 120#
5649	28"	Natural 175#



Band Hose Clamps

Part	Size	Band	Diameter
1495	#04	5/16"	1/4"-5/8"
1496	#06	5/16"	5/16"-7/8"
1499	#06	1/2"	3/8"-7/8"
1500	#08	1/2"	7/16"-1"
1501	#10	1/2"	1/2"-1 1/8"
1502	#12	1/2"	1/2"-1 1/4"
1556	#20	1/2"	3/4"-1 3/4"
3599	#24	1/2"	1"-2"



Hard Core Hose Reels

- Lightweight aircraft-grade aluminum disks and frame
- PVC spool & stainless hardware
- 316 Stainless steel core •Suitable for sodium hypochlorite



Part	Product
7029	HR12 reel
7030	HR 18 reel



Challenger

- Made in USA
- 4000 PSI maximum
- Viton swivel seals
- 225°F. maximum



Part	Hose	Cox Part	Dimensions
4988	100'	112-3-100	18x13x12
4990	250'	117-3-250	18x18x17

4063	6329-1-1	Brake bearing
5977	1935	Swivel 3/8 FPT
5993	1935seal	1935 repair kit



Competitor

- 90° 1/2" FPT swivel
- 4000 PSI maximum
- 225°F. maximum



Part	Hose	Cox Part	Dimensions
4869	300'	1125-4-200	25x18x17
6980	450'	112-4-325	31x18x17

4129	7429-4	Drag brake
5979	439seal	Repair kit
2615	Locking	pin assembly



Hand Crank Reels

HPC Stainless Steel

All stainless steel hose reel that will hold up to 400 feet of 3/8" 3/8" hose or 300 feet of ag hose. Swivel for high or low speed options.



Part	Product
7132	3/8 x 200' 5000 PSI
7133	3/8 X 400' 5000 PSI
7130	1/2" X 150' 600 PSI
7131	1/2" X 300' 600 PSI



Swivel Reels

- Reels swivel 200°
- Axle prevents hose from kinking
- Adjustable friction brake eliminates back lash when rewinding hose
- Multi position collar with spring loaded lock pin allows reel to be positioned in a variety of psiitons and locked
- Hose guide allows for easy hose rolling and prevents kinking
- 1/2" FPT in/out
- 4000 PSI maximum
- 250°F. maximum



5701

Drop-In



Part	Product
5701	K01-2025 100'
5719	K01-0207 200'



5701

Wall Mount



Part	Product
5707	K01-2027 100'
5728	K01-0208 200'



Flat Surface Mount



Part	Product
5709	K01-2028 100'
5729	K01-0209 200'



Mount block

Mounts to any round or square tubing



Part	Product
5702	K01-2026 100'



WARNING: These products can expose you to nickel and Chromium which is known to the state of California to cause cancer and birth defects and other reproductive harm. For more information go to www.P65warnings.ca.gov

HOSE REELS



"A" Frame Reels

- Heavy duty
- 5000 PSI SS swivel
- Viton swivel o-ring
- Switchable swivel/handle
- 3/8" & 1/2" FPT I/O
- Drum friction brake
- Powder coating on reel
- Mount on wall, bench or pressure washer



Part	Product
7008	3/8" x 150' reel
7009	3/8" x 300' reel
7010	3/8" x 450' reel
2217	2103246 swivel 1/2"
2535	2103249 Swiv kit
3110	Hi-temp swiv kit
2255	Hand crank

Power Rewind Kit



Can be assembled with all three A-frame reels. DC 12 volt electric motor includes mounting bracket, ring gear and stainless steel hardware



Part	Product
7059	12v rewind kit

"A" Frame Accessories

Reel Guide Assembly



- Protects hose when being pulled out or on an angle
- 4 ways enclosed pinch-proof
- Stainless steel guides
- Corrosion resistant stainless steel hardware



Part	Product
7060	2100462 150' guide
7061	2100463 300' guide
7062	2100503 450' guide

Hose Reel Stacking Kit



- Fits up to 4 high
- Stainless steel hardware
- Fits all A-frame hose reels
- Reels sold separately
- Assembly required



Part	Product
7011	Stack 150' & 300'
7014	Stack 450' reels

Hose Reel Cart



- Flat free tires
- Reel sold separately
- Assembly required



Part	Product
7012	For 7009 reel only

Hand Carry Reel

Can be used as a standard hose reel with a 3/8" hose or as a sewer jetting reel with the optional sewer jetting kit and a 1/4" sewer hose.



- 3/8" x 100' hose
- 1/4" x 125' hose
- 5000 PSI rated swivel
- Nickel plated hose mounting
- 3/8" MPT inlet
- 3/8" FPT outlet



Sewer Jetting Kit



- Mounts to Hand carry hose reel
- Includes full flow ball valve
- 1/4" FPT inlet/outlet
- Glycerin filled gauge
- 3 sewer jetting nozzles



Part	Product
7016	Hand Carry reel
7064	210358 Jetting kit

Hand Crank



- Extend your hose life
- 4000 PSI maximum
- 3/8" I/O
- Mount on wall or bench
- Full flow swivel
- Powder coated
- 225°F. maximum



Swivel Wall Mount Kit

Easily mount HPC hose reels to the wall with locking swivel plate



Part	Product
5355	50' 3/8" MPT x 3/8" FPT
5430	100' 3/8" FPT x 3/8" FPT
5440	200' compact 3/8" MPT x 3/8" FPT
7063	2100379 Wall mount kit
4255	Handle assembly w/screws
5429	Swivel 3/4 M27MST & 3/8" FPT in 3/8" FPT out 4000 PSI
5428	Swivel 1/2" MPT x 3/8" FPT
6782	Swivel kit for 5428 & 5429
6753	Swivel o-ring kit for 5428 & 5429
2603	Hi temp swivel kit 5428 & 5429



Hand Crank



- 100' of 3/8" hose
- 1/2" inlet/outlet
- 3000 PSI maximum
- 325°F. maximum



Part	Product
4901	18006M

