

TYR Hook



Pull the TYR through the duct from above

Part	Product
5273	Hook



Manhole Cleaner

Clean manholes and get cleaning results like never before. Made of stainless steel with a guard plate for extra protection



- Inlet: 1/2" FPT
- Pressure: 5100 PSI
- Temperature: 250° F.
- 2 1/8" nozzles (not included)

Part	Mos #	Size
6520	81.047	16"



High Draw Acid



- Up to 20% draw
- 4500 PSI maximum
- 190°F. maximum
- 3/8" FPT inlet/outlet
- 1/4" hose barb port
- Adjustable

Part	Injector	GPM
5786	1.8mm	2-3
5668	2.1mm	3-5
5730	2.3mm	5-8
1966	Repair	kit
3845	Ceramic	ball



Adjustable High Draw Acid

- Up to 20% draw/mix ratio
- 3600 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet/outlet



Part	Injector	GPM
6634	1.8mm	2-3
6635	2.1mm	3-5
6636	2.3mm	5-8



Adjustable Acid

- Up to 20% draw rate
- 3000 PSI maximum
- 180°F. maximum
- 3/8" FPT inlet/outlet
- 1/4" hose barb chemical port



Part	Injector	GPM
1958	1.8mm	2-3
1959	2.1mm	3-5
1960	2.3mm	5-8
1966	Repair	kit



SUTTNER ST-62 Injector



- Adjustable orifice size 2 to 8 GPM
- Siphon rate approximately 10:1
- 194°F. maximum
- 3/8" FPT inlet/outlet
- 1/4" hose barb chemical port



ST-61 metering valve connects to the chemical inlet barb without special tools



Chemical flow can be metered and shut off remotely with the ST-66

Part	Product
1719	ST-62 injector
1956	St-61 meter valve
2381	ST-66 dual meter
3470	ST-62 repair kit



Chemical Adjustable

- 3200 PSI maximum
- 195°F. maximum
- 3/8" MPT inlet/outlet
- 1/4" hose barb port



Part	Injector	GPM
3140	1.5mm	1-2
2209	1.8mm	2-3
2210	2.1mm	3-5
2211	2.3mm	5-8
2222	Repair	kit



Chemical Adjustable

- 4500 PSI maximum
- 200°F. maximum
- 8 GPM maximum
- 1/4" hose barb port



MVR400 3/8MPT inlet/outlet

Part	Injector	GPM
6151	1.8mm	2-3
6152	2.1mm	3-5
6153	2.3mm	5-8



MVR410 3/8FPT in, 3/8MPT out

Part	Injector	GPM
6154	1.8mm	2-3
6155	2.1mm	3-5
6156	2.3mm	5-8



Robokim Adjustable

- 3200 PSI maximum
- 210°F. maximum
- 3/8" MPT inlet/outlet
- 1/4" hose barb port



Part	Injector	GPM
2041	#0	2.1-2.9
2042	#1	2.9-4.0
2043	#2	4.0-5.6
2044	#3	5.6-10
1270	Chem	kit
3846	Acid	kit
3845	Ceramic	ball





Fixed High Draw

- Up to 20%draw
- 3600 PSI maximum
- 300°F. maximum
- 3/8" MPT inlet/outlet



Part	Injector	GPM
6631	1.8mm	2-3
6632	2.1mm	3-5
6633	2.3mm	5-8

mecline Fixed Chemical

MVR400 3/8MPT inlet/outlet



Part	Injector	GPM
6157	1.8mm	2-3
6158	2.1mm	3-5
6159	2.3mm	5-8



MVR410 3/8FPT in, 3/8MPT out



Part	Injector	GPM
6160	1.8mm	2-3
6161	2.1mm	3-5
6162	2.3mm	5-8



Fixed High Draw

- Up to 20%draw
- 4500 PSI maximum
- 190°F. maximum
- 3/8" MPT inlet/outlet



Part	Injector	GPM
5188	1.8mm	2-3
6740	2.1mm	3-5
6741	2.3mm	5-8
1966	Repair kit	kit



Fixed chemical



Part	Injector	GPM
2366	1.8mm	2-3
2367	2.1mm	3-5
2368	2.3mm	5-8
2222	Repair kit	kit



Injector kits

- Adjustable injector
- Quick connect in & out
- 4 feet of polybraided hose
- Strainer w/check valve

Chemical injectors



Part	Injector	GPM
2212	1.8mm PA	2-3
2214	2.1mm PA	3-5
2216	2.3mm PA	5-8



Injector kits

Acid injectors



Part	Injector	GPM
5398	1.8mm GP	2-3
2178	1.8mm Adams	2-3
5421	2.1mm GP	3-5
2179	2.1mm Adams	3-5
5478	2.3mm GP	5-8
2180	2.3mm Adams	5-8



Robokim kits



Part	Injector	GPM
2193	#0 kit	2.1-2.9
2194	#1 kit	2.9-4.0
2195	#2 kit	4.0-5.6
2196	#3 kit	5.6-10.8



Quick Connect Injectors

Streamline your combination injector/quick connect assembly. Built-in 3/8" socket and 3/8" plug save you money on labor for assembly.



- 10% draw
- 3500 PSI maximum
- 190°F. maximum
- 1/4" hose barb



Part	Injector	GPM
4603	1.8mm chemical	2-3
4604	2.1mm chemical	3-5
4605	2.3mm chemical	5-8
5452	Repair kit	

SUTTNER Hi pressure injectors

Upstream injection

If you like the way soap is applied at a self-service car wash, this accessory is for you! Introduce detergents into the water system before the pump for high pressure application.



- Chemical hose and strainer
 - 160°F. maximum
 - 3/4" FGH inlet/3/4" MGH outlet
- Use of pressure reducing valve recommended*



Part	Injector
4508	ST64 1.5-4.0 GPM
4569	ST64 over 4.0 GPM
6887	Pressure reducing valve



WARNING: These products can expose you to lead, nickel and chromium which is known to the state of California to cause cancer and birth defects and other reproductive harm. For more information go to www.P65warnings.ca.gov

SAND BLAST

Commercial sand blast kits

For light to medium duty

- Specifications:**
- 8 GPM maximum
 - 3650 PSI maximum
 - 190°F. maximum
- Kit includes:**
- Carbide nozzle
 - 25' 1/2" polybraid hose
 - 18" wand pipe with qc plug
 - Sand probe



Part	Product
2340	3.5 kit
2642	4.5 kit
2643	5.5 kit
2644	6.0 kit
2645	Carbide tip
4902	3.5 orifice



Industrial sand blast kits

Heavy duty industrial grade kit. Removes coatings from almost any surface. Use on metal, heavy graffiti accumulations, paint preparation



Operate at 4 GPM @ 3000 PSI
to 8 GPM @ 5000 PSI

5 degree nozzles (not included)

Part	Product
4009	Sand blast kit
6503	Replacement nozzle
4112	1/4" 5 degree 4.0 nozzle
4290	1/4" 5 degree 5.0 nozzle
3755	1/4" 5 degree 5.5 nozzle



Deluxified Industrial sand blast



Kit includes:

- 1 piece tungsten carbide nozzle
- 20' 3/4" Spiraflex aggie hose
- 18" wand pipe w/side handle
- Sand probe
- Cast aluminum mixing body
- 3 1/4" 5 degree spray nozzles

Part	Product
4700	Sand blast kit



Replacement Parts

Part	Product
6503	Tungsten carbide nozzle 1 piece
5713	Mixing body cast aluminum
3879	Sand probe
5044	Orifice adapter
3749	Sandmizer adapter
5053	Thumb screw
6350	Gasket
3111	20' Spiraflex hose 3/4"
4698	18" steel wand pipe 1/4" mpt
1536	Side handle for 1/4" pipe
4112	1/4" 5 degree 4.0 nozzle
4290	1/4" 5 degree 5.0 nozzle
3755	1/4" 5 degree 5.5 nozzle
6315	22mm plug x 1/4" MPT
6312	22mm coupler x 1/4" MPT
2123	3/4" hose x 3/4" MPT barb
4499	Hose clamp #8



Poly 3 Way Ball Valves



Part	Product
2292	1/4" Barb



Plastic Ball Valves



- NSF listed
- 125 PSI maximum
- Viton seals

Part	Product
4600	1/4" hose barb
4401	3/8" hose barb



Low Pressure Valves



- Brass
- 600 PSI maximum
- Full port

Part	Product
2141	1/4" FPT
2142	3/8" FPT
2143	1/2" FPT
2144	3/4" FPT
3992	1" FPT
3993	1 1/4" FPT
3999	1 1/2" FPT



3 Way Ball Valves

- Forged brass



Part	Product
4524	1/4" FPT 400 PSI
4525	3/8" FPT 400 PSI
4192	1/2" FPT 400 PSI



- Chrome plated steel ball
- Zinc plated steel body
- 212°F. maximum

Part	Product
4731	3/8" FPT 7000 PSI
4721	1/2" FPT 7000 PSI



Metering Valve



- 1/4" FPT
- 4000 PSI maximum
- 300°F. maximum

Part
1296



Mini Metering Valve



- 1/4" FPT
- 350 PSI maximum
- 100°F. maximum
- 3 GPM maximum

Part
2464

